

4AA

XPP-5564RX/GX

INTRINSICALLY SAFE DUAL-LIGHT ANGLE LIGHT

NIGHTSTICK[®]
Life Depends on Light™

INTRANTDUO



TURBO

Best Price!

DUAL LIGHT TECHNOLOGY




Batteriestatusanzeige - grün zeigt volle Ladung an und leuchtet rot, wenn die Batterien fast leer sind



270 Lumen Flutlicht - breite Ausleuchtung bei präzisen 45° Winkel nach unten



Einfaches Drücken vom Schalter, selbstständiges Controlling von den separaten LEDs



Federbelasteter Clip und V-Ring zur Sicherung an der Einsatzkleidung.



AVAILABLE IN HI-VIZ GREEN.

280 LUMENS

NEW • NEU • NEW • NEU

INTRANTDUO**TURBO****DUAL-LIGHT ANGLE LIGHT****4AA****ITEM NUMBER/UPC**

XPP-5564RX (Red), 017398806275
XPP-5564GX (Green), 017398806268

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cETLus, ATEX, IECEx, NFPA

CASE MATERIAL

- PC/ABS

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 250L, 6 hrs. runtime
- LOW: 110L, 18 hrs. runtime

FLOODLIGHT

- HIGH: 270L, 8.5 hrs. runtime
- LOW: 120L, 28 hrs. runtime

DUAL-LIGHT

- 280L, 5.5 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 54,900
- LOW: 7,333

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 469m
- LOW: 171m

WATER RATING

- IP-67 (Dustproof and Waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
- WIDTH: 2.75 in (70 mm)
- DEPTH: 2.5 in (64 mm)
- HEAD DIAMETER: 2.75 in (70 mm)
- WEIGHT: 11 oz (312g with batteries)

BATTERY

- 4AA batteries (included)

WARRANTY

- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
- 4AA batteries
- Instruction manual

FL1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	250 LUMENS	110 LUMENS	280 LUMENS
	6h	18h	5.5h
	469m		
	54900cd		

Bayco Products, Inc. XPP-5564GX/RX
640 S. Sanden Blvd., Wylie, TX 75098



Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
For use with Bayco 5564-CARRIER with 4 AA Energizer Type
EN91, E91, Panasonic LR6/XWA or Duracell MN1500 batteries only



Intertek
ID 5012927
ELECTRICAL SAFETY
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV1 GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T4 Ga
ZONE 20 AEx ia IIC T135°C Da
Ⓜ II 1 G Ex ia IIC T4 Ga
Ⓜ II 1 D Ex ia IIC T135°C Da

Ex ia IIC T4 Ga
Ex ia IIC T135°C Da
IECEX: IECEX ETL 23.0048X
ATEX: ITS I24ATEX39286X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell Alkaline



SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

CERTIFIED

ace-tec

Sandweg 5 | 25899 Niebüll
Tel. 0 46 61 / 67 50 60
www.ace-tec.de | info@ace-tec.de

